

# Wet Chop Strands 8007

## Product Description

**Wet Chop Strands 8007** are manufactured in the EU by Nippon Electric Glass, are produced from a continuous filament strand and are designed for quick and easy dispersion in gypsum feeder systems. As a premier wet chop product for gypsum applications, The 8007 wet chop fiber glass is easy to process and offers excellent performance in the end-use application. It provides outstanding characteristics such as flow consistency, fiber dispersion and fiber distribution in end end-use applications. The 8007 wet chop fiberglass is designed for reinforcement of gypsum products.

## User Benefits

- Aqueous-based sizing optimizes for fiber dispersion.
- Supported by NEG's technical resources.
- Manufactured and available in the Europe.
- Manufacturing facilities operate quality management systems that comply with ISO 9001:2015 requirements.

Type of Fiber	E-Glass (ASTM D 578-05)
Type of Sizing	Silane
Nominal Fiber Diameter ( $\mu\text{m}$ )	16
Nominal LOI (%)	EU: 0.15
Nominal Moisture Content (%)	7.5
Nominal Chop Length (mm)	EU: 12

## Packaging

- 1,000 kg / 1,100 kg bigbags (dry weight)
- 20 kg PE bags (dry weight)

## Storage

The wet chopped strands should be stored in closed packaging at ambient temperature. After partial use of a bag the packaging should be re-sealed in order to prevent moisture loss and drying-out of the product. Because of the high moisture content of the fibers the product has a shelf life of 6 months, depending on storage conditions.

A first in first out stock control system will help to minimize the influence of adverse storage conditions and packaging damage.

## More Information

<https://www.neg.co.jp/inquiry/>

<https://www.neg.co.jp/en/inquiry/>